




BEAM APPARATUS

VDAS® SM1004

A benchtop frame with load cells and cantilevers for the study of deflection and forces on different types of beams for a wide range of supports and loads. Also demonstrates Young's modulus.



KEY FEATURES

- Ideal for student use and classroom demonstrations
- Made for maximum flexibility and ease of use for extensive range of experiments
- Simply supported and cantilever beam tests with up to four supports with any loading
- Three load cells with digital indicators measure reaction forces or act as rigid sinking supports
- Precision digital indicators for accurate deflection measurements
- Weights and hangers supplied to apply point loads
- Supplied with five different test beams



BEAM APPARATUS

VDAS® SM1004

DESCRIPTION

The Beam Apparatus allows an extensive range of experiments to cover virtually all course requirements relating to bending of beams. The basic unit provides facilities for supporting beams on simple, built-in and sinking supports, applying point loads, and measuring support reactions and beam deflections. It includes five different test beams. A pack of ten additional beams (SM1004a) is available for further experiments.

The Beam Apparatus can be used for an almost limitless number of experiments ranging from determination of the elastic modulus for beams of different materials, through to studies of continuous beams with any loading. Great care has been taken at the design stage to ensure maximum flexibility and ease of use.

The main frame of the apparatus consists of an upper cross-member carrying graduated scales and two lower members bolted to T-legs to form a rigid assembly. The three load cells and cantilever-support pillar slide along the lower members and can be clamped firmly in any position. The load cells have direct digital readout and each is fitted with a hardened steel knife edge which can be adjusted to set the initial level or to simulate a sinking support. Locking pins can convert each load cell to a rigid support when required.

The cantilever support is a rigid pillar with a sturdy clamping arrangement to hold the beams when built-in end conditions are required. Four weight hangers and a set of weights are supplied to apply static loads. Three digital indicators measure all beam deflections. The indicators mount on magnetic carriers that slide along the upper cross-member. The indicators, carriers, load cells and weight hangers all have cursors that register on the scale (located on the upper cross-member) to ensure easy, accurate positioning. All digital indicators and load cells have sockets and cables for connection to TecQuipment's optional Versatile Data Acquisition System (VDAS®).

The standard test beams are in three thicknesses and include three different materials. They are suitable for the complete range of experiments covering different loading and support configurations. The optional set of beams provide for experiments on different types of beam including compound, channel and non-uniform beams of various materials.

For quick and reliable tests, TecQuipment's optional VDAS® gives accurate real-time data capture, monitoring and display, calculation and charting of all important readings on a computer (computer not included).

LEARNING OUTCOMES

- Verification of the bending equation
- Determination of flexural rigidity and elastic modulus (Young's modulus)
- Verification of static equilibrium
- Deflection of beams on two simple supports with point loads
- Reciprocal properties for loads and deflection
- Simple and propped cantilevers with any loading
- Continuous beams, statically indeterminate cases for simply supported beams and cantilevers on more than two supports with any loading (including measurement of unknown reactions)
- Simply supported and cantilever beams with sinking supports

With the SM1004a additional beams, these additional experiments can be done:

- The effects of material and section shape on flexural rigidity
- Bending characteristics of a brass/steel compound beam, with and without shearing connection between the two layers
- Equivalent sections, characteristics of a metal-faced wooden beam
- Deflections on a non-uniform (tapered) beam or cantilever

STANDARD FEATURES

- Supplied with comprehensive user guide
- Five-year warranty
- Manufactured in accordance with the latest European Union Directives
- ISO9001 certified manufacturer

RECOMMENDED ANCILLARIES

- Bench-mounted version of the Versatile Data Acquisition System (VDAS-B)
- Set of Additional Beams (SM1004a)
- Set of Basic Composite Beams (SM1004d1)
- Set of Cored Composite Beams (SM1004d2)
- Set of Variable Stiffness Composite Beams (SM1004d3)

BEAM APPARATUS

VDAS® SM1004

DEFLEX®

DefleX® is a complimentary tool designed to introduce students to the concept and technique of Digital Image Correlation (DIC). This product is compatible with our DefleX®-2D product that uses one video camera and our DefleX®-3D product that uses two video cameras to track the movement of materials during a dynamic event. They are complete and compact systems for measuring full-field displacements and strains over a material's surface in two and three dimensions, offering students a digital blended learning experience as part of their engineering courses.

To find out more, click [here](#)

ESSENTIAL SERVICES

BENCH SPACE NEEDED:

2000 mm x 600 mm

OPERATING CONDITIONS

OPERATING ENVIRONMENT:

Laboratory

STORAGE TEMPERATURE RANGE:

-25°C to +55°C (when packed for transport)

OPERATING TEMPERATURE RANGE:

+5°C to +40°C

OPERATING RELATIVE HUMIDITY RANGE:

80% at temperatures < 31°C decreasing linearly to 50% at 40°C

SOUND LEVELS

Less than 70 dB(A)

SPECIFICATIONS

TecEquipment is committed to a programme of continuous improvement; hence we reserve the right to alter the design and product specification without prior notice.

SM1004:

NETT DIMENSIONS AND WEIGHT:

2000 mm x 580 mm x 550 mm; 43 kg

PACKED DIMENSIONS AND WEIGHT:

0.63 m³; 120 kg (approximately)

DEFLECTION INDICATORS:

Digital Indicators with sockets for connection to VDAS®

LOAD CELL SUPPORTS:

Fitted with digital indicators with sockets for connection to VDAS®

FIVE TEST BEAMS SUPPLIED:

- 3 steel: 3.2 mm, 4.8 mm and 6.4 mm thick (nominal)
- 1 brass: 6.4 mm thick (nominal)
- 1 aluminium: 6.4 mm thick (nominal)

All beams are of nominal dimensions 19 mm wide x 1350 mm long

SM1004A SET OF ADDITIONAL BEAMS:

NETT DIMENSIONS AND WEIGHT:

600 mm x 15 mm x 310 mm; 3.5 kg

PACKED DIMENSIONS AND WEIGHT:

0.036 m³; 4 kg (approximately)

TEN TEST BEAMS SUPPLIED:

- 4 steel (1 tapered)
- 1 brass
- 1 steel and brass compound
- 2 aluminium (1 with channel cross-section)
- 1 hardwood
- 1 aluminium and wood compound

All beams are of different dimensions and cross-section