





≡ FOUR-STROKE PETROL ENGINE

TD201

Four-stroke, single-cylinder petrol engine for use with the Small Engine Test Set, available in pull and electric start (ES).



LONGCIN ENGINE
(ELECTRIC START)



KOHLER ENGINE



FUEL TANK

KEY FEATURES

- For safe and effective studies and demonstrations of a four-stroke, single-cylinder petrol engine
- For use with TecEquipment's Small Engine Test Set (TD200)
- High-quality yet cost-effective engine specially modified for educational use
- Wide range of investigations possible
- Quickly and accurately mounts on the test bed
- Includes colour-coded fuel tank with quick-release couplings
- Electric start option (TD201ES)

LEARNING OUTCOMES

When used with TecEquipment's Small Engine Test Set (TD200), investigations into the performance and characteristics of a four-stroke petrol engine, including:

- Torque, speed and power relationship
- Brake mean effective pressure
- Engine performance curves
- Air and fuel consumption
- Volumetric and thermal efficiencies



FOUR-STROKE PETROL ENGINE

TD201

DESCRIPTION

High-quality and cost-effective four-stroke, single-cylinder petrol engine for use with TecQuipment's Small Engine Test Set (TD200). Adapted specially for education to enable effective laboratory testing and demonstrations, the engine includes an exhaust thermocouple, a half-coupling to link to the test set dynamometer and all essential hoses and fittings. In addition, each engine includes a colour-coded fuel tank with self-sealing couplings. The couplings ensure the engine can be connected and disconnected quickly and efficiently with minimum loss or spillage of fuel. For convenience and safety, the fuel tank can be removed for filling or for storage in a fuel locker when not in use. Removing the fuel tank also prevents unauthorised use of the equipment.

The engine is mounted on a sturdy precision bed plate. The bed plate has dowels and slots which align and locate it accurately with the dynamometer test set. This minimises the time spent replacing one engine with another.

This engine starts using a simple pull cord, however TecQuipment can supply an electric start version (TD201ES). The electric start version is supplied with a suitable cable to connect to the optional battery (TD200b) or another suitable battery. Contact our sales team for details.

The TD200 test bed is supplied with a 2.5 m exhaust. All TecQuipment engines are supplied with a 1" BSP threaded stub adaptor for connection to the TD200 exhaust. Alternatively the user can connect their own adaptor and connect to their laboratory exhaust.

STANDARD FEATURES

- Supplied with comprehensive user guide
- Five-year warranty
- Made in accordance with the latest European Union directives
- ISO9001 certified manufacturer

OPERATING CONDITIONS

OPERATING ENVIRONMENT:

Well ventilated laboratory

STORAGE TEMPERATURE RANGE:

-25°C to +55°C (when packed for transport)

OPERATING TEMPERATURE RANGE:

+5°C to +40°C

OPERATING RELATIVE HUMIDITY RANGE:

80% at temperatures < 31°C decreasing linearly to 50% at 40°C

NOISE LEVELS:

The noise level produced by this engine may exceed 70 dB, therefore TecQuipment strongly recommends the use of suitable ear defenders.

ESSENTIAL BASE UNIT

- Small Engine Test Set (TD200)

RECOMMENDED ANCILLARIES

- 12 V Battery (TD200b) for the electric start (ES) model only

SPECIFICATIONS (SAMPLE ONLY)

TecQuipment is committed to a programme of continuous improvement; hence we reserve the right to alter the design and product specification without prior notice.

DIMENSIONS:

MODEL	KOHLER	LONGIN
TD201 / ES	500 mm (width) 430 mm (height) 400 mm (depth)	460 mm (width) 400 mm (height) 360 mm (depth)

Packed: 0.13 m³

WEIGHT:

MODEL	KOHLER	LONGIN
TD201	22 kg Nett	18 kg Nett
TD201ES	27 kg	21 kg
PACKED	27 kg (32 kg ES Model)	23 kg (26 kg ES Model)

FUEL:

Gasoline up to 10% ethyl alcohol and 90% unleaded

MODEL	KOHLER	LONGIN
ENGINE CAPACITY	208 cc	196 cc
NET POWER	4.5 kW at 3600 rev.min ⁻¹	4.1 kW at 3600 rev.min ⁻¹
NET TORQUE	12.5 Nm at 2800 rev.min ⁻¹	12.4 Nm at 2500 rev.min ⁻¹
SPEED	Governed to approximately 3600 rev.min ⁻¹	Governed to approximately 3600 rev. min ⁻¹
COOLING	Air Cooled	Air Cooled

NOTE:

- All values stated are approximate and subject to variation
- The engines supplied have very similar or equivalent specifications to that used by TecQuipment to generate the sample results. However, some performance variations will occur.
- The characteristics of some engines may vary as the latest emission regulations come into force
- For the latest performance information please refer to the engine manufacturer's website.